




## FT 306A

### FEATURES:

- High tack adhesive
- Broad range of service temperature
- Specially designed adhesive
- Strong yet conformable plastic carrier
- Easy release liner

### BENEFITS:

- The good wetting and shear laminating adhesive provides a perfect initial adhesion to various smoothing and polishing materials
- Suitable where final application involves both low and high temperature environments
- Excellent adhesion to a variety of metals, rigid and foamed plastics
- Provides excellent dimensional stability
- Reinforcement of flexible substrates
- Facilitates easy removal at point of application



### CONSTRUCTION:

#### Adhesive:

Permanent synthetic rubber adhesive

#### Carrier:

15 micron clear polypropylene film

#### Liner:

Blue-green glassine

## FT 306A

Physical Properties	Typical Values	
<b>THICKNESS</b>		
Adhesive + Carrier	87 microns	
Liner	85 microns	
Total	172 microns	
*ATM.7		
<b>TACK</b>	1200 N/m	
*ATM.8		
<b>ADHESION (180° peel) N/m</b>	<b>20 min</b>	<b>24 hrs</b>
Stainless Steel	920	970
Polycarbonate	800	900
Painted Steel	760	820
Rigid Polypropylene	520	660
*ATM.1		
<b>SHEAR RESISTANCE</b>		
(static - 1000g/25mm x 25mm)	666 min	
*ATM.2		
<b>TEMPERATURES</b>		
Application (minimum)	+10°C	
Service (continuous)	-40°C to +110°C	
Short term	+130°C	
*TEST METHODS		

Note: The listed values are typical only and not intended to serve as product specifications

## APPLICATION TECHNIQUES

- It is essential with all pressure-sensitive tapes the application surface is clean, dry and free of grease and oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (firm / rigid) surface achieves different performance

## STORAGE AND SHELF LIFE

The shelf life of the product is two years when stored at 18-22°C / 64-72°F, 30-70% relative humidity and out of direct sunlight, in original packaging.

Please refer to [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com) for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2012 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. Avery™, AFB™ and all other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Performance  
Tapes

**Asia Pacific**  
Kunshan, China,  
NO. 618 Nanhe Road  
Kunshan Economic &  
Technological Zone  
China 215335  
Phone: +86 512 57155001  
Fax: +86 512 57155059

**Europe**  
Tieblokkenlaan 1  
B-2300 Turnhout  
Belgium  
Phone: +32 (0)14 40 48 11  
Fax: +32 (0)14 40 48 55

**South America**  
Rua Francisco Foga, 225  
13280-000 Vinhedo  
SP Brazil  
Phone: +55 19 3876 7736  
Fax: +55 19 3876 7682

**North America**  
250 Chester Street  
Painesville, Ohio  
44077 USA  
Phone: +1 866-462-8379  
Fax: +1 888-358-4469

For more information on our bonding tapes and adhesive solutions, visit [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com)