




## FT 7206

### FEATURES:

- Specially designed adhesive with Excellent flow properties
- Low density open tissue
- Easy release liner

### BENEFITS:

- Provides excellent immediate bond to PU and PE foams, metals and apolar plastics
- Ensures very good adhesion, even to low density foams
- Whilst offering a reasonable dimensional stability, the product offers a high degree of conformability
- Facilitates easy one step removal at point of application



### CONSTRUCTION:

#### Adhesive:

Permanent synthetic rubber adhesive

#### Carrier:

Tissue

#### Liner:

White glassine

## FT 7206

Physical Properties	Typical Values
<b>THICKNESS</b>	
Adhesive + Carrier	105 microns
Liner	60 microns
Total	165 microns
*ATM.7	
<b>ELONGATION</b>	2.0 %
<b>TENSILE STRENGTH</b>	1.1 kN/m
*ATM.13 - ASTM D882	
<b>TACK (finat)</b>	1400 N/m
*ATM.8 - FINAT.9	
<b>ADHESION (180° peel) N/m</b>	<b>24 hrs</b>
Stainless Steel	1200
Painted Steel	1150
Polycarbonate	1150
Rigid Polypropylene	1150
*ATM.1 - PSTC.1	
<b>SHEAR RESISTANCE</b>	
(static - 2500g/25mm x 25mm)	833 min
*ATM.2 - FINAT.8 - PSTC.7	
<b>TEMPERATURES</b>	
Application (minimum)	+10°C
Service (continuous)	-40°C to +60°C
Short term	+70°C
*TEST METHODS	

Note: The listed values are typical only and not intended to serve as product specifications

### APPLICATION TECHNIQUES

- It is essential with all pressure-sensitive tapes the application surface is clean, dry and free of grease and oil
- Bond strength is dependent upon the amount of adhesive-to-surface contact developed
- Note that different pressure, time and temperature on different (firm / rigid) surface achieves different performance

### STORAGE AND SHELF LIFE

The shelf life of the product is two years when stored at 18-22°C / 64-72°F, 30-70% relative humidity and out of direct sunlight, in original packaging.

Please refer to [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com) for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2012 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. Avery™, AFB™ and all other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.



Performance  
Tapes

**Asia Pacific**  
Kunshan, China,  
NO. 618 Nanhe Road  
Kunshan Economic &  
Technological Zone  
China 215335  
Phone: +86 512 57155001  
Fax: +86 512 57155059

**Europe**  
Tieblokkenlaan 1  
B-2300 Turnhout  
Belgium  
Phone: +32 (0)14 40 48 11  
Fax: +32 (0)14 40 48 55

**South America**  
Rua Francisco Foga, 225  
13280-000 Vinhedo  
SP Brazil  
Phone: +55 19 3876 7736  
Fax: +55 19 3876 7682

**North America**  
250 Chester Street  
Painesville, Ohio  
44077 USA  
Phone: +1 866-462-8379  
Fax: +1 888-358-4469

For more information on our bonding tapes and adhesive solutions, visit [Tapes.AveryDennison.com](http://Tapes.AveryDennison.com)